

# 5500 Air drill specifications

<b>Base Size</b>	60 ft (18.3 m)	70 ft (21.3 m)
------------------	----------------	----------------

Spacing Options		
<b>10 in (25.4 cm)</b>		
Number of shanks	72	84
Working Width ft (m)	60 ft (18.3 m)	70 ft (21.3 m)
<b>12 in (30.5 cm)</b>		
Number of shanks	60	70
Working Width ft (m)	60 ft (18.3 m)	70 ft (21.3 m)

Frame widths		
Main Frame	10 ft (3.1 m)	10 ft (3.1 m)
Inner Wing	15 ft (4.6 m)	15 ft (4.6 m)
Outer Wing	10 ft (3.1 m)	15 ft (4.6 m)
Transport Width	17 ft 8 in (5.4 m)	17 ft 8 in (5.4 m)
Transport Height (max)	13 ft 6 in (4.1 m)	13 ft 6 in (4.1 m)

Tyres		
Centre Frame Castors	11 L x 15 (D)	11 L x 15 (D)
Inner Wing Castors	11 L x 15 (D)	11 L x 15 (D)
Outer Wing Castors	11 L x 15 (D)	11 L x 15 (D)
Rear Transport Wheel*	11 L x 15 (D)	11 L x 15 (D)

\*A single tyre is used unless machine is configured with 6.5 in (16.5 cm) pneumatic, then those wheels are used for transport.

Press Wheels Options			
Rubber	3 in x 22 in (7.6 cm x 55.9 cm)	Steel	3.5 in x 22 in (8.9 cm x 55.9 cm)
	4 in x 22 in (10.2 cm x 55.9 cm)		4.5 in x 22 in (11.4 cm x 55.9 cm)
	5.5 in x 22 in (14 cm x 55.9 cm)	Pneumatic	6.5 in (16.5 cm)

<b>Depth Control</b>	Each wing follows ground independently with flexibility front to rear with single point depth setting
<b>Packing Pressure Adjustment</b>	Adjustable packing pressure